RE 22282-XC Edition: 2019-10 Replaces: 04.16 RA78498479_AA



Directional spool valves, direct operated, with fluidic actuation

Type WPXC, WHXC



Features

- ▶ 4/3, 4/2 or 3/2-way version
- For intended use in potentially explosive atmosphere
 Porting pattern according to ISO 4401-03-02-0-05
- (with or without locating hole)
- Operating methods:
 - pneumatic (WP)
 - hydraulic (WH)

- Size 6
- ► Component series 5X, 6X
- ▶ Maximum operating pressure 315 bar
- ▶ Maximum flow 60 l/min

CE

ATEX units For potentially explosive atmospheres



Information on the explosion protection:

- Area of application in accordance with the Explosion Protection Directive 2014/34/EU: IM2, II2G, II2D
- Type of protection valve:
 - Ex h I Mb X according to EN 80079-38
 - Ex h IIC T6...T4 Gb X according to EN 80079-36
 - Ex h IIIC T80°C...T100°C Db X according to EN 80079-36
- Contents

Features	1
Ordering code	2
Symbols	3
Operating methods	4
Function, section	5
Technical data	6,7
Characteristic curves	8
Performance limits	9,10
Dimensions	11, 12
Further information	13

Notice: The documentation version with which the product was supplied is valid.

Ordering code

01	02	03	04	05	06	07		80	09	10		11	12	13
	W			6			/			XC	/			

01	3 main ports	3
	4 main ports	4
02	Directional valve	W

Type of actuation

03	Pneumatic	Р
	Hydraulic	Н
04	Ports, radial	no code
	I	
05	Size 6	6
06	Symbols; possible version see page 3 and 4	
07	Component series 50 59 (50 59: unchanged installation and connection dimensions) - version "H"	5X
	Component series 60 69 (60 69: unchanged installation and connection dimensions) - version "P"	6X

Spool return

08	With spring return	no code
	Without spring return	0
	Without spring return with detent	OF
09	Without manual override	no code
	With manual override	N ¹⁾

Explosion protection

10	"Non-electrical devices"	ХС
	For details, see information on the explosion protection page 7	
11	Without throttle insert	no code
	Throttle Ø 0.8 mm	B08 ²⁾
	Throttle Ø 1.0 mm	B10 ²⁾
	Throttle Ø 1.2 mm	B12 ²⁾
	Throttle Ø 1.2 mm	

Seal material (observe compatibility of seals with hydraulic fluid used, see page 7)

12	NBR seals	no code
	FKM seals	V
13	Without locating hole	no code
	With locating hole and locking pin ISO 8752-3x8-St	/62

¹⁾ Only version "P"

 $^{2)}\;$ Use if flow > performance limit of the valve, effective in channel P.

Spool positions

Ordering	Spool p	ositions	Ver	Version		
code	2 pos.	3 pos.	"P"	"H"		
no code	1	1	1	1		
0	1	-	1	✓		
OF	1	-	1	1		

Symbols







1) Example:

Symbol E with spool position "a" \rightarrow ordering code ..**EA**.. Symbol E with spool position "b" \rightarrow ordering code ..**EB**..

If Notes:

Representation according to DIN ISO 1219-1. Hydraulic interim positions are shown by dashes.

Operating methods

	Ordering code	9	Type of a	actuation
Symbol	Actuating side	Spool return	"P" (pneumatic)	"H" (hydraulic)
			$ \begin{array}{c c} $	-
A, C, D		/0	$ \begin{array}{c c} A & B \\ a & b \\ P & T \end{array} $	$ \begin{array}{c c} A & B \\ \hline a & b \\ \hline P & T \\ \end{array} $
		/OF		
В, Ү			A B a b b W a b< P T	A B a b b W a b
	"a" ¹⁾ = .A		$ \begin{array}{c c} A & B \\ \hline a & a & 0 \\ P & T \\ \end{array} $	$ \begin{array}{c c} A & B \\ \hline a & a & 0 \\ \hline P & T \\ \end{array} $
E, G, H, J, M	"b" ¹⁾ = .B		A B 0 b P T	A B b W 0 b
			A B a b b P T	A B a b b P T

¹⁾ See symbols on page 3

Function, section

General information

Valves of type WP...XC and WH...XC are fluidically actuated directional spool valves. They control start, stop and direction of flow.

The directional valves basically consist of housing (1), one or two types of actuation (2) (hydraulic, pneumatic actuation cylinder), the control spool (3), and one or two return springs (4). The connections for the control are arranged radially (type WP) (5). The bleeding ports (6) must be connected and led to a place outside the potentially

explosive area. In the de-energized condition, the control spool (3) is held in the central or initial position by the return springs (4) (except for impulse spools).

The control spool (3) is moved to the desired spool position by means of the operating methods.

5 5 2 6 Type 4WP 6 E6X/...XC/... Α b 5 2 3 Hananal DUDUUY В

Type 4WH 6 E5X/...XC/.... Α

Without spring return, with detent "OF"

Directional valves with hydraulic or pneumatic operation are also available as 2-spool position valve with detent (7). If actuation elements with detent are used, each spool position can be fixed.

Without spring return "O"

If actuation elements without return springs and without detent are used, there is no defined spool position in the non-operated condition.



Type 4WP 6 C6X/OF/N...XC/...^A

Throttle insert

The use of a throttle insert is required when due to prevailing operating conditions, flows can occur during the switching processes, which exceed the performance limit of the valve.



Technical data

(for applications outside these values, please consult us!)

		"P"	"H"		
1 actuation cylinder	kg	approx. 1.8	approx. 2.0		
2 actuation cylinders	kg	approx. 2.0	approx. 2.2		
Installation position		any 1)			
Ambient temperature range °C		C −20 +80			
Storage temperature range		+5 +40			
Maximum storage time Year		s 1			
Maximum admissible acceleration a max		g 10			
Surface protection		Galvanized			
re	°C	See information on explosion protection, page 7			
	 1 actuation cylinder 2 actuation cylinders ration a_{max} 	 ▶ 1 actuation cylinder ▶ 2 actuation cylinders kg ▶ 2 actuation cylinders C °C Years ration a_{max} g rre °C 	P" ▶ 1 actuation cylinder kg approx. 1.8 ▶ 2 actuation cylinders kg approx. 2.0 any 1) any 1) °C -20 +80 °C +5 +40 Years 1 ration a _{max} g 10 Galvanized Galvanized		

Hydraulic						
Maximum operating pressure	▶ Port P, A, B	bar	315			
	► Port T		 With symbols A or B, port T connection if the operating admissible tank pressure. 2 bar minimum preload pressure 	must be used as leakage oil pressure exceeds the essure required.		
Minimum pilot pressure		bar	4 (see characteristic curve page 8)	6 10 > tank pressure $^{2)}$		
Maximum pilot pressure		bar	10	200		
Pilot volume		cm ³	4.24	1.23		
Maximum flow		l/min	n 60			
Flow cross-section	▶ Symbol Q	Symbol Q mm ² approx. 6% of nominal cross-section				
(spool position 0)	► Symbol W	mm ²	² approx. 3% of nominal cross-section			
Hydraulic fluid			see table page 7			
Hydraulic fluid temperature range		°C	−20 +80 (NBR seals) −15 +80 (FKM seals)			
Viscosity range		mm²/s	\$ 2.8 500			
Maximum admissible degree of contamination of the hydraulic fluid, cleanliness class according to ISO 4406 (c)			Class 20/18/15 ³⁾			
Maximum switching frequency		1/h	7200			

¹⁾ With version "O" (symbol A, C and D) horizontal

- ²⁾ Performance limits dependent on the minimum pilot pressure, see page 10
- ³⁾ The cleanliness classes specified for the components must be adhered to in hydraulic systems. Effective filtration prevents faults and simultaneously increases the life cycle of the components.

Available filters can be found at www.boschrexroth.com/filter.

Technical data

(for applications outside these values, please consult us!)

Hydraulic fluid		Classification	Suitable sealing materials	Standards	Data sheet
Mineral oils		HL, HLP, HLPD	NBR, FKM	DIN 51524	90220
Bio-degradable	Insoluble in water	HETG	FKM	100 15290	Standards Data sheet DIN 51524 90220 ISO 15380 90221 ISO 15380 90221 ISO 15380 90223
		HEES	FKM	150 15380	90221
	Soluble in water	HEPG	FKM	ISO 15380	7
Flame-resistant	 Containing water 	HFC (Fuchs: Hydrotherm 46M, Renosafe 500; Petrofer: Ultra Safe 620; Houghton: Safe 620; Union: Carbide HP5046)	NBR	ISO 12922	90223

Important information on hydraulic fluids:

► For further information and data on the use of other hydraulic fluids, please refer to the data sheets above or contact us.

- There may be limitations regarding the technical valve data (temperature, pressure range, life cycle, maintenance intervals, etc.).
- The ignition temperature of the hydraulic fluid used must be 50 K higher than the maximum surface temperature.
- Bio-degradable and flame-resistant containing water: If components with galvanic zinc coating (e.g. version "J3" or "J5") or parts containing zinc are used, small amounts of dissolved zinc may get into the hydraulic system and cause accelerated aging of the hydraulic fluid. Zinc soap may form as a chemical reaction product, which may clog filters, nozzles and solenoid valves – particularly in connection with local heat input.

Flame-resistant – containing water:

- Due to increased cavitation tendency with HFC hydraulic fluids, the life cycle of the component may be reduced by up to 30% as compared to the use with mineral oil HLP. In order to reduce the cavitation effect, it is recommended – if possible specific to the installation – to back up the return flow pressure in ports T to approx. 20% of the pressure differential at the component.
- Dependent on the hydraulic fluid used, the maximum ambient and hydraulic fluid temperature must not exceed 50 °C. In order to reduce the heat input into the component, a maximum duty cycle of 50% in continuous operation has to be set for on/off valves (measuring period 300 s). If this is not possible due to the function, an energy-reducing control of these components is recommended, e.g. via a PWM plug-in amplifier.

Information on explosion protection			
Area of application according to Directive 2014/34/EU	IM2	ll2G	ll2D
Type of protection of valve according to EN 80079-36 / EN 80079-38 ⁴⁾	EX h I Mb X	Ex h IIC T6 T4 Gb X	Ex h IIIC T80°C T100°C Db X
Maximum surface temperature ⁵⁾ °C	100		
Temperature class ⁶⁾	-	T6 T4	-
Temperature ⁷) °C	-	-	80 100

 $^{\rm 4)}\,$ Ex h: structural safety c according to EN 80079-37.

- ⁵⁾ Surface temperature > 50 °C, provide contact protection.
- ⁶⁾ The specification T4 refers to the maximum hydraulic fluid and ambient temperature. At hydraulic fluid and ambient temperature up to a maximum of 60 °C, use in temperature class T6 is possible.
- ⁷⁾ The maximum surface temperature of 100 °C refers to the maximum hydraulic fluid and ambient temperature. At hydraulic fluid and ambient temperature up to a maximum of 60 °C, the maximum surface temperature is reduced to 80 °C.

IFF Special application conditions for safe application:

- Maximum admissible dust layer thickness according to EN 60079-14.
- With version "P", the port for control may only be connected to a pressure supply with compressed air according to ISO 8573-1:2010 (7:4:4). For the generation of the compressed air, no air from the explosive area must be used.
- ▶ The ports to control and bleeding must not exceed a maximum air volume of 900 cm³. (Prevention of an ignition of gas with leaky lines.)

Characteristic curves

(measured with HLP46, 9_{oil} = 40 ±5 °C)

$\Delta p - q_V$ characteristic curves



Symbols	Direction of flow			
	P-A	P-B	A-T	B-T
Α	3	3	-	-
В	3	3	-	-
С	1	1	3	1
D	5	5	3	3
E	3	3	1	1
G	6	6	7	7
Н	2	4	2	2
J	1	1	2	1
М	2	4	3	3
Y	5	5	3	3

7 Symbol "H" in central position ($P \rightarrow T$)



Minimum pilot pressure dependent on the tank pressure (version "P")

If Notice:

With higher tank pressures, the minimum pilot pressure must be raised according to this diagram.

Performance limits: Version "P" (measured with HLP46, **9**_{oil} = 40 ±5 °C)

IF Notice:

The specified switching power limits are valid for operation with two directions of flow (e.g. from P to A and simultaneous return flow from B to T). Due to the flow forces acting within the valves, the admissible switching power limits may be considerably lower with only one direction of flow (e. g. from P to A while port B is blocked).In such use cases, please consult us.



Characteristic curve	Symbol	
1	А, В	
2	A/O, C, C/O, D, D/O, E, G, H, J, M, Y	

Performance limits: Version "H"

(measured with HLP46, ϑ_{oil} = 40 ±5 °C)

See notes page 9.



Pilot pressure 6 bar > tank pressure			
Spring return	Characteristic curve	Symbol	Sp
	1	Α, Β	
"no code"	2	C, D, Y	(with
(with spring return)	3	E, J, M	
	4	G, H	
"0"	F		
"OF"	5	A, C, D	

Pilot pressure 10 bar > tank pressure			
Spring return	Characteristic curve	Symbol	
"no code"	1	А, В	
(with spring return)	5	C, D, Y, E, G, H, J, M	
"0"	F		
"OF"	5	A, C, D	

Dimensions: Version "P" (dimensions in mm)



- 1 ► Valve with 2 spool positions and 2 actuation cylinders
 ► Valve with 3 spool positions and 2 actuation cylinders
- 2 Actuation cylinder "a"
- 3 Actuation cylinder "b"
- 4 Plug screw for valve with one actuation cylinder (2 spool positions)
- 5 Identical seal rings for ports P, A, B, T
- 6 Name plate
- 7 Porting pattern according to ISO 4401-03-02-0-05 (with or without locating hole)

Valve mounting screws (separate order)

Only use valve mounting screws with the subsequently listed thread diameters and strength properties. Observe the screw-in depth. **4 hexagon socket head cap screws**

ISO 4762 - M5 x 50 - 10.9

(friction coefficient **µ**_{total} = 0.09 ... 0.14); Material no. **R913043758** **Subplates** (separate order) with porting pattern according to ISO 4401-03-02-0-05 see data sheet 45100.

Œ

69

If Notes:

45

- Subplates are no components in the sense of Directive 2014/34/EU and can be used after the manufacturer of the overall system has conducted an assessment of the risk of ignition. The "G...J3" versions are free from aluminum and/or magnesium and galvanized.
- The dimensions are nominal dimensions which are subject to tolerances.

Dimensions: Version "H"

(dimensions in mm)



- Valve with 2 spool positions and 2 actuation cylinders
 Valve with 3 spool positions and 2 actuation cylinders
- **2** Actuation cylinder "a"
- **3** Actuation cylinder "b"
- 4 Cover for valve with one actuation cylinder (2 spool positions)
- 5 Identical seal rings for ports P, A, B, T
- 6 Name plate
- 7 Porting pattern according to ISO 4401-03-02-0-05 (with or without locating hole)

Valve mounting screws (separate order)

Only use valve mounting screws with the subsequently listed thread diameters and strength properties. Observe the screw-in depth.

4 hexagon socket head cap screws

ISO 4762 - M5 x 50 - 10.9 (friction coefficient μ_{total} = 0.09 ... 0.14); Material no. **R913043758**



Subplates (separate order) with porting pattern according to ISO 4401-03-02-0-05 see data sheet 45100.

🕼 Notes:

- Subplates are no components in the sense of Directive 2014/34/EU and can be used after the manufacturer of the overall system has conducted an assessment of the risk of ignition. The "G...J3" versions are free from aluminum and/or magnesium and galvanized.
- The dimensions are nominal dimensions which are subject to tolerances.

Further information

- Data sheet 45100 Subplates ▶ Hydraulic fluids on mineral oil basis Data sheet 90220 Environmentally compatible hydraulic fluids Data sheet 90221 ► Flame-resistant, water-free hydraulic fluids Data sheet 90222 ► Flame-resistant hydraulic fluids - containing water (HFAE, HFAS, HFB, HFC) Data sheet 90223 ▶ Directional spool valves, direct operated, with manual actuation
- Selection of filters
- ► Information on available spare parts

- Operating instructions 22282-XC-B
- www.boschrexroth.com/filter
- www.boschrexroth.com/spc

Notes

Bosch Rexroth AG Industrial Hydraulics Zum Eisengießer 1 97816 Lohr am Main, Germany Phone +49 (0) 93 52/40 30 20 my.support@boschrexroth.de © All rights reserved to Bosch Rexroth AG, also regarding any disposal, exploitation, reproduction, editing, distribution, as well as in the event of applications for industrial property rights.

The data specified above only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification.

It must be remembered that our products are subject to a natural process of wear and aging.

Notes

Bosch Rexroth AG Industrial Hydraulics Zum Eisengießer 1 97816 Lohr am Main, Germany Phone +49 (0) 93 52/40 30 20 my.support@boschrexroth.de © All rights reserved to Bosch Rexroth AG, also regarding any disposal, exploitation, reproduction, editing, distribution, as well as in the event of applications for industrial property rights.

The data specified above only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification.

It must be remembered that our products are subject to a natural process of wear and aging.

Notes

Bosch Rexroth AG Industrial Hydraulics Zum Eisengießer 1 97816 Lohr am Main, Germany Phone +49 (0) 93 52/40 30 20 my.support@boschrexroth.de © All rights reserved to Bosch Rexroth AG, also regarding any disposal, exploitation, reproduction, editing, distribution, as well as in the event of applications for industrial property rights.

The data specified above only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification.

It must be remembered that our products are subject to a natural process of wear and aging.